

Compressor

- R290
- R134a
- R404A



EM / R290



FF / R134a



NT / R404A



NEU / R404A

Model	Refrigerant	Appl.	Cooling Capacity			Displ. (cc)	HP	COP W/W	Voltage	Test Condition	Motor Type
			Btu/h	Kcal/h	Watt						
EMX3117U	R290	L/MBP	676	170	198	4.50		1.61	220-240	ASHRAE LBP	RSCR
EM2X3121U	R290	L/MBP	938	236	275	5.54	1/4+	1.74	220-240	ASHRAE LBP	RSCR
EMX3125U	R290	L/MBP	1000	252	293	6.09		1.66	220-240	ASHRAE LBP	RSCR
EMX3134U	R290	L/MBP	1385	349	406	7.95		1.65	220-240	ASHRAE LBP	RSCR
			3930	990	1152			2.91		ASHRAE HBP	
EMY3134U	R290	L/MBP	1327	334	389	7.95		1.56	220-240	ASHRAE LBP	RSIR
EMX3140U	R290	L/MBP	1644	414	482	9.50		1.62	220-240	ASHRAE LBP	RSIR
			4561	1149	1336			2.70		ASHRAE HBP	
NEU6217U	R290	MBP	6714	1692	1967	14.28	3/4	2.76	220-240	ASHRAE HBP	CSCR
NT6220U	R290	MBP	7678	1935	2250	17.39	3/4	2.79	220-240	ASHRAE HBP	CSCR

Model	Refrigerant	Appl.	Cooling Capacity			Displ. (cc)	HP	COP W/W	Voltage	Test Condition	Motor Type
			Btu/h	Kcal/h	Watt						
FF8.5HBK	R134a	L/M/HBP	662	167	194	7.95	1/4	1.11	220-240	ASHRAE LBP	CSIR
			2880	726	844			2.49		ASHRAE HBP	
FF110HAK	R134a	L/MBP	850	214	249	9.04	1/3	1.30	220-230	ASHRAE LBP	CSIR
FF112HBK	R134a	L/M/HBP	1090	275	319	11.14	1/3+	1.25	220-240	ASHRAE LBP	CSIR
			4492	1132	1316			2.61		ASHRAE HBP	
FFU160HAX	R134a	L/MBP	1299	327	381	12.92	1/2	1.43	220-240	ASHRAE LBP	CSIR
NEU6212Z	R134a	HBP	4927	1242	1444	14.28	1/2	2.36	220-240	ASHRAE HBP	CSIR
NEU6214Z	R134a	HBP	5582	1407	1636	16.8	1/2	2.14	220-240	ASHRAE HBP	CSIR

Model	Refrigerant	Appl.	Cooling Capacity			Displ. (cc)	HP	COP W/W	Voltage	Test Condition	Motor Type
			Btu/h	Kcal/h	Watt						
NEU2140GK	R404A	LBP	1639	413	480	8.77	1/2	1.34	220-240	ASHRAE LBP	CSIR
NEU2155GK	R404A	LBP	2247	566	658	12.11	3/4	1.32	220-240	ASHRAE LBP	CSIR
NEU2168GK	R404A	LBP	2539	640	744	14.28	3/4	1.27	220-240	ASHRAE LBP	CSIR
NT2178GK	R404A	LBP	2738	690	802	17.39	1-	1.42	220-240	ASHRAE LBP	CSCR
NEU2178GK	R404A	LBP	3065	772	898	16.8	1	1.4	220-240	ASHRAE LBP	CSCR
NT2180GK	R404A	LBP	3350	844	982	20.44	1	1.34	220-240	ASHRAE LBP	CSCR
NT2192GKA	R404A	LBP	3716	936	1089	22.37	1 1/4	1.41	220-240	ASHRAE LBP	CSCR
NT2212GK	R404A	LBP	4684	1180	1373	27.80	1 1/2	1.37	220-240	ASHRAE LBP	CSCR
NEU6215GK	R404A	MBP	6582	1659	1929	12.11	3/4	2.23	220-240	ASHRAE HBP	CSIR
NEU6220GK	R404A	MBP	7747	1952	2270	14.28	3/4	2.17	220-240	ASHRAE HBP	CSCR
NT6222GK	R404A	MBP	8492	2140	2488	17.39	1	2.26	220-240	ASHRAE HBP	CSCR
NT6226GK	R404A	MBP	11450	2885	3355	22.37	1+	2.44	220-240	ASHRAE HBP	CSCR
NTU6240GKV	R404A	MBP	15215	3834	4458	27.8	1 1/2	2.66	220-240	ASHRAE HBP	CSCR

Test Condition

ASHRAE LBP : Evaporation -23.3°C, Condensing 54.4°C, Return Gas 32.2°C, Ambient 32.2°C, Subcooling 22.2K
 ASHRAE HBP : Evaporation 7.2°C, Condensing 54.4°C, Return Gas 35°C, Ambient 35°C, Subcooling 8.3K

Update : 202304V2



CONTACT US:
0707 607 807



www.coolmax.vn

